



RESIDENTIAL



DISABLED  
USE



# THE APOLLO

Water Hydraulic Residential Lift

## MAIN SPECIFICATIONS

- Carrying Capacity:** 250kg
- Car Size:** 900W x 1300D x 2000Hmm
- Door Size:** 870W x 2035Hmm
- Maximum Travel:** 3500mm
- Lift Speed:** 0.093m/sec with a 90kg load
- Max No. of Stops:** 2 Stops
- Drive System:** Water hydraulic with direct acting cylinders on each side of the lift car
- Minimum Pit Depth:** 80mm
- Cylinder Extension:** Distance of travel plus 300mm
- Machine Cabinet:** 605W x 335D x 1800Hmm
- Controls:** Automatic buttons & key isolation
- Standards:** Meets or exceeds requirements of the Australian Standards Lift code AS1735 Part 17
- Usage:** Residential
- Application:** Internal or external
- Installation:** Crane in, dismantle or man handle.
- Cladding:** Can be either attached directly to the tower or fitted into an owners supplied lift shaft.
- Supply Voltage:** 240volt. Single Phase. 16amp RCD protected

 07 3274 4211

### Call Us - We're Here to Help

We have an unrivalled reputation for after-sales care and customer service. Call us and one of our friendly lift specialists will gladly answer all your questions.

Aussie Lifts Pty Ltd  
 12 Achievement Crescent  
 Acacia Ridge  
 Queensland 4110  
 Tel (07) 3274 4211  
 Fax (07) 3274 5543  
 info@aussielifts.com.au  
 www.aussielifts.com.au  
 Built to Australian Standards  
 A.C.N # 100 798 703  
 A.B.N # 92 516 686 505  
 Q.B.S.A # 1025986  
 E.C.A # 54227

© 2011 by Aussie Lifts Pty Ltd. All Rights Reserved. This brochure is for information purposes only. Information may change without notice. All dimensions and specifications are a guide only and must NOT be used for construction purposes. All changes must be in compliance with the lift code and the manufacturer reserves the right to approve or refuse any changes.

**AUSSIE LIFTS**

**AUSSIE LIFTS**



**“Perfect for new construction or retrofitting, the Apollo can easily be incorporated into a two level home for independent living. Being custom built, the size of the lift and it’s operation can be altered to suit individual needs.”**

Originating from the basic concept of using water to hoist a platform, the Apollo has evolved into a lift that is purposely built for disable use.

Custom built, special consideration can be made with the operation of the lift through different style buttons, automatic dialling telephone and door operators.

Able to travel 3.5 metres, lifting a 90kg load at 0.093m/sec, the Apollo has the capacity to carry 250kg easily.

Offering flexibility for tight spaces, the size of the lift can be reduced by altering the lift structure. The self supporting lift tower also means cladding can be attached directly to the lift.

To help compliment the decor of your home, the Apollo has a number of cosmetic options available when it comes to landing doors and the lift car lining.

In addition, the lift is jam packed with an array of safety features and is a breeze to install. Therefore, you can’t go wrong by selecting an Apollo when trying to stick to a budget.

**Cost Effective**

- ▶ Self supporting lift tower - no load bearing walls required
- ▶ Low installation / home construction costs
- ▶ Low running costs / power consumption
- ▶ Single phase 240v power
- ▶ Once a year maintenance
- ▶ Suitable for internal or external installation

**Safety**

- ▶ Automatic emergency battery backup lowering system
- ▶ Additional manual lowering facilities
- ▶ Battery backup in-lift lighting system
- ▶ Internal phone
- ▶ Emergency stop function
- ▶ Infra-red safety sensors
- ▶ Key lockable push button controls
- ▶ Hydraulic low pressure detection switch
- ▶ Automatic homing of the lift car
- ▶ Non return breather

**Peace of Mind**

- ▶ Manufactured by a family owned and operated company
- ▶ Australian made to Australian Standards
- ▶ Built to superior specifications using quality materials
- ▶ 12 month parts and labour warranty
- ▶ Lift delivered, installed & tested by qualified lift technicians
- ▶ Custom built to your specifications
- ▶ Lift tower can be finished to match home decor
- ▶ Unrivalled after-sales service
- ▶ Environmentally friendly

**LIFT TOWER**

Built as a free-standing, self-supporting unit and weighing approx 350kg, the lift tower is fabricated from aluminium and comes complete with doors, door jambs, flashings, electrical wiring and hydraulic cylinders.

Depending on space and architectural needs, the lift shaft can be set up for cladding to be applied directly to it’s own frame work.

To create a flush running surface between the landings, each lift is fitted with a panel between the landing doors preventing the need for any lift car doors.

**LIFT CAR**

Available in two styles of configuration:

- ▶ Single entry **“A Model”** with entry and exiting on the same side
- ▶ Dual entry **“B Model”** with entry at the front and exiting via the rear.

Lift cars can be individually built to the customer’s requirements - up to a maximum floor space of 1.3m<sup>2</sup> or supplied in the standard size of 900mm wide x 1300mm deep x 2000mm high.



**Why buy Australian Made?**

- ▶ Built to Australian Standards
- ▶ Confidence in Quality
- ▶ Short lead times
- ▶ Parts readily available
- ▶ Jobs created in Australia
- ▶ Supporting Australian Economy
- ▶ Profits remain in Australia
- ▶ Ensuring skills are retained for future generations



**LIFT CAR INTERIOR**

Available in a number of interior finishes, the most popular being white colorbond trimmed with extruded aluminium, the Apollo can also be finished in Tasmanian oak, MDF and Stainless steel.

Standard car features include:

- ✓ Stainless steel handrail
- ✓ Non - slip floor covering indoor/outdoor carpet
- ✓ Recessed emergency telephone
- ✓ 2 x recessed down lights
- ✓ 2 x photo electric sensors across the door entrance

**LANDING DOORS**

Fitted with swing action doors with a mechanical lock, adjustable automatic door closer and electrical interlock. The whole assembly is part of the lift shaft.

Door styles include:

- ✓ Redicote flush door with optional glass view panel
- ✓ Pattern doors from the Hume/ Corinthian internal door range
- ✓ Metal door with optional glass view panel
- ✓ Glass door

To assist in the operation of the doors, door hold open devices, automatic door operators or sensory operation can be fitted to the landing doors as an optional extra.

Door size for **standard** lift car: 870mm wide x 2040mm high. Lift can be supplied with 2340mm high doors.

**STATIONS**

Mounted at the front of the lift and onto a stainless steel plate, the Apollo has the option of two button styles:

- ▶ Square protruding plastic buttons
- ▶ Round stainless steel buttons


For securing the lift against unwanted users, each control is fitted with an isolating key switch. Used in conjunction with the parking facility, the lift car will position itself just above the lower landing, preventing either of the landing doors from being opened. This command can be overridden at either landing by keying the lift back on.

**MACHINE CABINET**

The Apollo uses a separate lift machine cabinet that creates a more compact lift shaft design and eliminates costly machine room construction.

Fabricated from metal, and powdercoated, to withstand the external elements, the cabinet is mounted at the ground level for easy access for emergency and maintenance purposes.

Provided with a key lockable door, the cabinet contains the hydraulic power unit, recyclable water tank, hydraulic control valves, electrical control board, emergency power supply, cabinet lighting, emergency tools and instructions.



**INSTALLATION**

The lift tower can be dismantled, man-handled or crane in depending on the home’s access and architecture. The lift comes complete with it’s own tower and can be fitted to an owner supplied shaft or clad directly to the tower (cladding is to be in compliance with the lift code). No load bearing walls are required.

**ELECTRICAL REQUIREMENTS**

The standard models all have the same economical power requirements.

- ▶ 240volt. Single Phase. 16amp RCD protected
- ▶ Active analogue telephone line

**MAINTENANCE**

For optimum performance, reliability and long term use, the lift should be serviced every 12 months by an approved lift technician.

**WARRANTY**

The lift equipment provided is covered for 12 months, excluding malicious damage and/or misuse.

