

# ADIS

A U T O M A T I C   D O O R S

I N T R O D U C E S

## NGA SERIES

**HEAVY DUTY AUTOMATIC SLIDING DOOR OPERATORS  
FOR ALUMINIUM DOORS**



**STRONGER ► QUIETER ► COMPACT**



The AUSTRALIAN Automatic Door Company

# The Company

ADIS AUTOMATIC DOORS is a fully Australian owned and operated company.

The name ADIS simply means, Automatic Door Installation Services. The company has over 35 years of experience in the Automatic Doors Industry.

ADIS philosophy is provide a high quality product at a competitive price backed by the highest standard of back up service to achieve total customer satisfaction. The introduction of the Next Generation Series of Automatic Door operators is a major advancement in automatic doors technology in the Australian and global automatic door markets. This series includes the most advanced features available in the world.

ADIS research and design team have developed the NG series of door equipment to ensure maximum performance, durability and reliability, plus compatibility with the new Australian Standard AS 5007-2007 and European Standard DIN 18650-1:2005.

ADIS Automatic Doors have been successful in achieving the AUSTRALIAN DESIGN AWARD for excellence in product design & excellence in product efficiency.



Security airlock for banks




Foyers for apartments



Shopping centres



Cinemas & Theaters



Office security screens



Retail outlets



Hospitals & Medical Centres




Pedestrian traffic control doors



Wholesale outlets

**FRAMED GLASS ENTRIES**



## Features:

- Slim line Modern Design
- Australian Made
- Designed for New Standards
- Compact Modular Motor Design
- High Security Electric Locking
- No Exposed Wiring
- Energy Efficient Low Power Consumption

## Quiet Operation

Tracking system is dual linear, which is designed for high security and long life service. The carriage assemblies are fitted with unique track wheels that eliminates the possibility of the doors disengagement from the track.

## Advanced Technology


ADIS utilizes the latest in digital microprocessor technology, giving the control unit multiple programmable modes including: - provision to interface with building security system, monitoring the doors position and locks status, built-in UPS. The microprocessor operating parameters can be adjusted to accommodate various climatic conditions and specific site requirements in relation to speed, braking etc. Safety is a priority: The ADIS microprocessor will automatically reverse operation while the door is closing, should the doors be obstructed. Photo electric or active infrared safety sensors are recommended to focus across the doorway to halt and open the doors immediately upon the sensor detecting an obstruction.

## Programmable

Optional remote monitoring and control system (MACS) to check door status or make operational adjustments.

## Pelmet Hinge

The ADIS pelmet design features a unique interlocking hinge to provide secure closure and maximum cover even when mounted hard up against the ceiling.




## High Security Locking

The Next Generation Series operators utilizes a purpose built motor which includes an electric locking system to ensure that the doors can be securely fixed in any position. This method of locking ensures the highest level of security.



# COMPARE ADIS ADVANTAGES

- ADIS is Australian owned and Australian manufactured.
- Slim line modern design only 132 mm in overall track height.
- Compact modular design of motor drive system.
- Latest digital microprocessor controller to gain more exact control of the door operator, Provision to interface with building security systems.
- Over engineered to take total door weights of up to 250Kg (max door weight of 125 Kg).
- The main transom housing is hard coated anodized to give smooth operation of the exclusive dual track system.
- No exposed wiring due to concealed wiring system.
- Built in UPS (Uninterrupted Power Supply) can allow doors to continue to operate under a power failure when doors are locked. This is a standard feature in ADIS NGA operator not an extra.
- Improved multiple safety features to ensure maximum user safety.
- High security electric motor locking.
- Zone activation sensor system that uses latest presence detection technology to improve overall safety.
- Unique interlocking cover pelmet which prevents any chances of pelmet cover dislodging from the main track system. An added safety feature.



## BACK UP SERVICE

- Fully qualified technicians to meet our high standard of company service.
- A complete 24 hour, 7 days a week, ongoing preventive maintenance service.
- Extensive nationwide service network via our 1800 number.

## TECHNICAL SPECIFICATIONS

Opening width maximum	4000 mm	Exit only function	Yes
Operator length up to	8000 mm	Battery Backup	Yes
Total combined weight for bi-parting doors	250 Kg	UPS when locked	Yes
Door weight per leaf	125 Kg	UPS in all conditions	Optional
Opening speed per double leaf variable	25-1300 mm/sec	Open closed positional signal	Optional
Closing speed per double leaf variable	25-1300 mm/sec	High security electric locking	Optional
Door open dwell time, variable	0-60 sec	Locked / unlocked signal	Yes
Manual opening/ closing force	<30 N	Open closed positional signal	Yes
Operator size height/depth	132 mm / 155 mm	Memory setting retained without power	Yes
Fail safe/ fail secure	Yes / Yes	Operating Power	24 Volts
Airlock function	Yes	Appliance Rating	40 Watts
Press closed function	Yes	Memory setting retained without power	Yes
Climate control (reduced opening) function	Yes	Power supply	240V/10Amp
Noise attenuation	32 db	Solar power operation	Optional
Keypad control	Optional		
Safety stop	Yes		
Safety return	Yes		
Safety beam shut off when closed	Yes		
Fire alarm activation	Yes		
Chime outlet	Yes		



3/413 VICTORIA STREET - WETHERILL PARK NSW 2164 AUSTRALIA

PHONE: +612 9757 4600 - FAX: +612 9757 4233

TOLL FREE: 1800 600 602

EMAIL: [info@autodoors.com.au](mailto:info@autodoors.com.au)

VISIT OUR WEBSITE: [www.autodoors.com.au](http://www.autodoors.com.au)